

Rec'd PCT/PTO 02 JUN 2000
09/509928

1

RESISTOR AND ITS MANUFACTURING METHOD

INSA17

FIELD OF THE INVENTION

5

The present invention relates to the field of resistors used for detecting current in a current-carrying circuit as a voltage, and their manufacturing method.

10

BACKGROUND OF THE INVENTION

The conventional resistor of this type is disclosed in Japanese Laid-open Patent Publication No. H6-20802.

A conventional resistor is described below with reference to drawings.

15

Fig. 29 (a) is a perspective, and Fig. 29 (b) is a sectional view of the conventional resistor.

20

In Figs. 29 (a) and (b), a resistor element 1 is a rectangular parallelepiped resistance metal made of an alloy of nickel, chromium, aluminum, and copper, and it has an integrated structure with opposing ends 2 and 3. A conductive material such as solder is coated on both ends 2 and 3 of the resistor element 1, typically by plating, to form terminals 4 and 5. A central portion 6 is the central area of the resistor element 1, excluding the terminals 4 and 5, and this central portion 6 is bent against the terminals 4 and 5 in order to create a gap between the resistor and a substrate when the resistor is mounted on the substrate. An insulating material 7 is provided on the central portion 6 of the resistor element 1.

25

A method for manufacturing the conventional resistor configured as above is described below.

Figs. 30 (a) to 30 (e) are process charts illustrating the manufacturing method of the conventional resistor. In Fig. 30 (a), the rectangular parallelepiped resistor element 1 having an integrated structure made of an alloy of nickel, chromium, aluminum, and copper with a predetermined resistance is formed.

In Fig. 30 (b), a conductive material 8 is plated on the entire face of the resistor element 1 (not illustrated).

In Fig. 30 (c), the conductive material 8 coated on the central portion 6 of the resistor element 1 is scraped off with a wire brush so as to expose the resistor element 1 at the central portion 6.

In Fig. 30 (d), the terminals 4 and 5 disposed at the sides of the resistor element 1 are bent downward against the central portion 6 of the resistor element 1.

Lastly, in Fig. 30 (e), the central portion 6 of the resistor element 1 is covered with an insulating material 7 by molding to complete the conventional resistor.

The above conventional resistor achieves the integrated structure of the resistor element 1 and terminals 4 and 5 by bending the resistance metal, and the resistor element 1 is made of an alloy of nickel, chromium, aluminum, and copper. The terminals 4 and 5 are configured by plating a conductive material such as solder on the surface of both ends 2 and 3.

The electrical conductivity of the alloy of nickel, chromium, aluminum, and copper configuring the resistor element 1 has lower electrical conductivity than metals generally having good conductivity such as copper, silver, gold, and aluminum. Since the base material of the terminals 4 and 5 is made of the same alloy as that of the resistor element 1, the base material configuring the terminals 4

and 5 has a larger resistance in proportion to its smaller electrical conductivity compared to metals generally having good conductivity. Accordingly, both ends 2 and 3 of the resistor element 1 are coated, such as by plating, with a conductive material such as solder in order to reduce resistance.

5 In the case of resistors having large resistance in the conventional configuration, resistance at the terminals 4 and 5 is reduced by coating a conductive material such as solder on the surface of both ends 2 and 3 of the resistor element 1, and thus the difference in resistance between the resistor element 1 and terminals 4 and 5 becomes extremely large. Consequently, the composite resistance of the
10 resistor element 1 and terminals 4 and 5, which is the overall resistance of the resistor, may be represented by only the resistance of resistor element 1, allowing to ignore the resistance at the terminals 4 and 5.

000220"02550550
15 However, in the case of resistors with a resistance of 0.1 ohms or below, the resistance of the terminals 4 and 5 in the entire resistor cannot be ignored. For accurate measurement of the resistance of a resistor with a high resistance, the four-probe method is generally used. However, for measuring the resistance of a resistor with a resistance of 0.1 ohms or below, the resistance varies according to the position of the probe contacting the terminals 4 and 5, even the four-probe method is used, because the resistance of the terminals 4 and 5 affect the resistance of the entire
20 resistor with increasing resistance of the terminals 4 and 5. In this case, fluctuation in resistance due to deviation in the measuring point on the terminals 4 and 5 increases as the proportion of the resistance of the terminals 4 and 5 in the entire resistor increases. Accordingly, it is necessary to specify the measuring point for reproducing measurements with high accuracy in the conventional configuration.
25 However, assuring the reproducibility of the same measuring point is extremely

difficult even when the measuring point is specified, thus decreasing the reproducibility of the resistance measurements.

SUMMARY OF THE INVENTION

The present invention aims to address the above disadvantage of the prior art, and provides a resistor which assures highly accurate measurement of resistance even if the measuring point is not precisely placed.

To solve the aforementioned disadvantage of the conventional resistor, the resistor of the present invention comprises a sheet metal resistor element and separate metal terminals electrically connected to both ends of the sheet resistor element. These terminals are made of metal having the same or greater electrical conductivity than that of the resistor element.

With the above configuration, resistance of the terminals can be made smaller than that of the resistor element because the terminals are made of a material having the same or greater electrical conductivity than that of the resistor element. This enables to reduce the proportion of resistance of the terminals in the entire resistor, allowing to ignore its effect on fluctuation of resistance due to deviation in measuring points of a resistance measuring terminal. The present invention can thus assure reproducibility of highly accurate measurement of resistance, providing the resistor which assures highly accurate measurement of resistance even if the measuring point is not precisely placed.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 (a) is a sectional view of a resistor in accordance with a first exemplary embodiment of the present invention.

Fig. 1 (b) is a plan view of the resistor in accordance with the first exemplary embodiment of the present invention.

Fig. (c) is a side view of a terminal, a key part, of the resistor in accordance with the first exemplary embodiment of the present invention seen from an open side.

Figs. 2 (a) to 2 (d) are process charts illustrating a method for manufacturing the resistor in accordance with the first exemplary embodiment of the present invention.

Fig. 3 is a sectional view of another example of the resistor in accordance with the first exemplary embodiment of the present invention.

Fig. 4 (a) is a sectional view of a resistor in accordance with a second exemplary embodiment of the present invention.

Fig. 4 (b) is a plan view of the resistor in accordance with the second exemplary embodiment of the present invention.

Fig. 5 is a sectional view of a resistor in accordance with a third exemplary embodiment of the present invention.

Fig. 6 is a side view of a terminal, a key part, of a resistor in accordance with a fourth exemplary embodiment of the present invention seen from an open side.

Fig. 7 (a) is a sectional view of a resistor in accordance with a fifth exemplary embodiment of the present invention.

Fig. 7 (b) is a plan view of the resistor in accordance with the fifth exemplary embodiment of the present invention.

Figs. 8 (a) to 8 (d) are process charts illustrating a method for manufacturing the resistor in accordance with the fifth exemplary embodiment of the present invention.

Fig. 9 (a) is a sectional view of a resistor in accordance with a sixth exemplary embodiment of the present invention.

Fig. 9 (b) is a plan view of the resistor in accordance with the sixth exemplary embodiment of the present invention.

Fig. 10 (a) is a sectional view of a resistor in accordance with a seventh exemplary embodiment of the present invention.

Fig. 10 (b) is a plan view of the resistor in accordance with the seventh exemplary embodiment of the present invention.

Fig. 11 (a) is a sectional view of a resistor in accordance with an eighth exemplary embodiment of the present invention.

Fig. 11 (b) is a plan view of the resistor in accordance with the eighth exemplary embodiment of the present invention.

Fig. 11 (c) is a side view of a terminal, a key part, of the resistor in accordance with the eighth exemplary embodiment of the present invention seen from an open side.

Fig. 12 is a side view of another example of a terminal of the resistor in accordance with the eighth exemplary embodiment of the present invention seen from an open side.

Fig. 13 (a) is a sectional view of a resistor in accordance with a ninth exemplary embodiment of the present invention.

Fig. 13 (b) is a plan view of the resistor in accordance with the ninth exemplary embodiment of the present invention.

Fig. 14 (a) is a sectional view of a resistor in accordance with a tenth exemplary embodiment of the present invention.

Fig. 14 (b) is a plan view of the resistor in accordance with the tenth exemplary embodiment of the present invention.

5 Fig. 14 (c) is a sectional view of a terminal cut widthwise of the resistor in accordance with the tenth exemplary embodiment of the present invention.

Fig. 15 (a) is a sectional view of a resistor in accordance with an eleventh exemplary embodiment of the present invention.

10 Fig. 15 (b) is a plan view of the resistor in accordance with the eleventh exemplary embodiment of the present invention.

Fig. 16 is a sectional view of a resistor in accordance with a twelfth exemplary embodiment of the present invention.

Fig. 17 is a sectional view of a resistor in accordance with a thirteenth exemplary embodiment of the present invention.

15 Fig. 18 is a sectional view of a resistor in accordance with a fourteenth exemplary embodiment of the present invention.

Figs. 19 (a) to 19 (c) are process charts illustrating a method for manufacturing the resistor in accordance with the fourteenth exemplary embodiment of the present invention.

20 Fig. 20 (a) is a sectional view of a resistor in accordance with a fifteenth exemplary embodiment of the present invention.

Fig. 20 (b) is a plan view of a surface of the resistor in accordance with the fifteenth exemplary embodiment of the present invention.

25 Fig. 20 (c) is a plan view of a rear face of the resistor in accordance with the fifteenth exemplary embodiment of the present invention.

0000270 00000000

Fig. 21 (a) is a sectional view of a resistor in accordance with a sixteenth exemplary embodiment of the present invention.

Fig. 21 (b) is a plan view of the resistor in accordance with the sixteenth exemplary embodiment of the present invention.

5 Fig. 22 is a sectional view of another example of the resistor in accordance with the sixteenth exemplary embodiment of the present invention.

Fig. 23 is a sectional view of a resistor in accordance with a seventeenth exemplary embodiment of the present invention.

10 Fig. 24 (a) is a sectional view of a resistor in accordance with an eighteenth exemplary embodiment of the present invention.

Fig. 24 (b) is a plan view of the resistor in accordance with the eighteenth exemplary embodiment of the present invention.

15 Figs. 25 (a) to 25 (e) are process charts illustrating a method for manufacturing the resistor in accordance with the eighteenth exemplary embodiment of the present invention.

Fig. 26 (a) is a sectional view of a resistor in accordance with a nineteenth exemplary embodiment of the present invention.

Fig. 26 (b) is a plan view of the resistor in accordance with the nineteenth exemplary embodiment of the present invention.

20 Fig. 26 (c) is a sectional view taken along Line A-A in Fig. 26 (b).

Figs. 27 (a) to 27 (e) are process charts illustrating a method for manufacturing the resistor in accordance with the nineteenth exemplary embodiment of the present invention.

25 Fig. 28 (a) is a sectional view of a resistor in accordance with a twentieth exemplary embodiment of the present invention.

0000270 82550550

Fig. 28 (b) is a plan view of the resistor in accordance with the twentieth exemplary embodiment of the present invention.

Fig. 28 (c) is a sectional view taken long Line B-B in Fig. 28 (b).

Fig. 29 (a) is a perspective of a conventional resistor.

Fig. 29 (b) is a sectional view of the conventional resistor.

Figs. 30 (a) to 30 (e) are process charts illustrating a method for manufacturing the conventional resistor.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

First exemplary embodiment

A resistor in a first exemplary embodiment is described below with reference to drawings.

Fig. 1 (a) is a sectional view of the resistor in the first exemplary embodiment of the present invention. Fig. 1 (b) is a plan view of the resistor, and Fig. 1 (c) is a side view of a terminal, a key part of the resistor, seen from the open side.

In Figs. 1 (a) to 1 (c), a resistor element 11 is made such as of a sheet of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy. First and second terminals 12 and 13 have a concave groove 14 of a width k which is equivalent to a thickness T of the resistor element 11, and are provided and electrically connected to both ends of the resistor element 11. The thickness t of these first and second terminals 12 and 13 is thicker than the thickness T of the resistor element 11; their width m is equivalent to or wider than the width W of the

resistor element 11; and their length w is shorter than the length L of the resistor element 11. The first and second terminals 12 and 13 are made of metals such as copper, silver, gold, aluminum, copper nickel, or copper zinc with the same or greater electrical conductivity than that of the resistor element 11.

5 A manufacturing method of the resistor in the first exemplary embodiment of the present invention as configured above is described next with reference to drawings.

Figs. 2 (a) to 2(d) are process charts illustrating the manufacturing method of the resistor in the first exemplary embodiment of the present invention.

10 In Fig. 2 (a), a metal sheet or metal strip such as of copper, silver, gold, aluminum, copper nickel, and copper zinc having electrical conductivity equivalent to or greater than the resistor element 11 (not illustrated) is formed into the first and second terminals 12 and 13 having the concave groove 14, using a range of processes including cutting, casting, forging, pressing, and drawing. The first and second
15 terminals are formed in a way to achieve the next dimensions: Width k of the concave groove 14 equivalent to the thickness T of the resistor element 11, thickness t thicker than the thickness T of the resistor element 11, width m equivalent to or wider than the width W of the resistor element 11, and the length w shorter than the length L of the resistor element 11.

20 In Fig. 2 (b), a metal sheet or metal strip such as of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy is formed into the resistor element 11 having a predetermined sheet shape and predetermined resistance, calculated from the volume resistivity, section area, and length, through a range of processes including cutting, punching, and pressing.

In Fig. 2 (c), after fitting both ends of the resistor element 11 into the groove 14 of the first and second terminals 12 and 13, the first and second terminals 12 and 13 are heat pressed in the vertical direction (in the direction of holding the resistor element 11).

5 In Fig. 2 (d), a protective film 16 made of a film such as of epoxy resin, polyimide resin, or poly-carbodiimide resin is cut into a predetermined shape by means of punching and pressing, and is placed on the top and bottom of the resistor element 11 (not illustrated). The protective film 16 is formed on the top, bottom, and side faces of the resistor element 11 by thermal compression bonding or
10 ultrasonic welding to complete the resistor in the first exemplary embodiment of the present invention.

The direction of inserting both ends of the resistor element 11 into the groove 14 of the first and second terminals 12 and 13 may be from the open side of the first and second terminals 12 and 13 or from the side face of the first and second terminals
15 12 and 13.

For adjusting the resistance of the resistor in the first exemplary embodiment of the present invention, a through groove may be created on the resistor element 11 or a part of the surface and/or side face of the resistor element 11 may be cut by laser, punching, diamond wheel cutting, grinding, etching, or the like while measuring the
20 resistance between predetermined points or calculating the required processing after measuring the resistance. The resistance may also be adjusted or corrected at the time of forming the resistor element 11.

If a material with a lower electrical conductivity than the resistor element 11 is used for the first and second terminals 12 and 13 in the resistor as manufactured
25 above, deviations in the resistance due to variations in the position of measuring

point are magnified, making it inappropriate for practical use. Accordingly, the first and second terminals 12 and 13 are made of a material having electrical conductivity equivalent to or greater than that of the resistor element 11.

Deviations in resistance due to the position of measuring point may also be reduced by making the thickness t of the first and second terminals 12 and 13 greater than the thickness T of the resistor element 11. In particular, the thickness t of the first and second terminals 12 and 13 may be required to be three times or more greater than the thickness T of the resistor element 11 to achieve allowable dispersion in resistance fully satisfying in-house specification.

Fig. 3 shows another example of a resistor in the first exemplary embodiment of the present invention.

In Fig. 3, a third conductive metal layer 15 is provided between the resistor element 11 and the first terminal 12 and between the resistor element 11 and the second terminal 13 to provide an electrical connection between the resistor element 11 and the first terminal 12, and between the resistor element 11 and the second terminal 13. For bonding the resistor element 11 and the first and second terminals 12 and 13, a range of methods may be used: (1) welding; (2) brazing after inserting a third conductive metal such as copper, silver, gold, tin, and solder between the resistor element 11 and the first and second terminals 12 and 13; (3) plating the resistor element 11 and first and second terminals 12 and 13, and thermal compression bonding after fitting the resistor element 11 into the first and second terminals 12 and 13; and (4) applying conductive paste to the resistor element 11 and the first and second terminals, and then thermosetting after fitting the resistor element 11 into the first and second terminals 12 and 13.

Second exemplary embodiment

A resistor in a second exemplary embodiment of the present invention is described below with reference to drawings.

Fig. 4 (a) is a sectional view, and Fig. 4 (b) is a plan view of the resistor in
 5 the second exemplary embodiment of the present invention.

In Figs. 4 (a) and 4 (b), a resistor element 17, made typically of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy, is corrugated in the thickness direction. First and second terminals 18 and 19 have a concave groove 20 of the width k which is equivalent to the thickness T of the resistor element 17, and
 10 are provided and electrically connected to both ends of the resistor element 17. The thickness t of these first and second terminals 18 and 19 is thicker than the total thickness V of the resistor element 17; their width m is equivalent to or wider than the width W of the resistor element 17; and their length w is shorter than the length L of the resistor element 17. The first and second terminals 18 and 19 are made of
 15 metals such as copper, silver, gold, aluminum, copper nickel, or copper zinc with the same or greater electrical conductivity than that of the resistor element 17.

A manufacturing method of the resistor in the second exemplary embodiment of the present invention as configured above is described next with reference to drawings.

20 The manufacturing method of the resistor in the second exemplary embodiment is the same as that described for the resistor in the first exemplary embodiment using Fig. 2. A metal sheet or strip such as of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy is formed into the resistor element 11 having a predetermined sheet shape and predetermined resistance,
 25 calculated from the volume resistivity, section area, and length, through a range of

processes including cutting, punching, and pressing. A detail which differs from the first exemplary embodiment is that, after forming the resistor element 11 as described above, a sheet of resistor element 11 is corrugated in the thickness direction in accordance with dimensions required for the resistor, so as to form the resistor element 17.

The resistance of the resistor in the second exemplary embodiment may be increased by bending the resistor element 17 in such a way that the length L of the resistor element 17 is increased in the longer side direction. On the other hand, the resistance of this resistor may be reduced by rotating it 90°, that is to bend it in a way so that its width W becomes longer.

When the resistor element 17 is bent in the width W direction, some other changes in its shape may be required. More specifically, the first and second terminals 18 and 19 may require a broader width k for the groove 20 to match the total thickness V in the bending direction of the resistor element 17. Or, the edge of the resistor element 17 may not be bent in order to fit the resistor element 17 into the original width k of the groove 20.

Third exemplary embodiment

A resistor in a third exemplary embodiment of the present invention is described below with reference to a drawing.

Fig. 5 is a sectional view of the resistor in the third exemplary embodiment of the present invention.

In Fig. 5, a resistor element 21 is made typically of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy. An insulating sheet 22, made such as of alumina, glass, glass fiber impregnated epoxy resin, or paper

0950928 072000

impregnated phenolic resin, has the same dimensions as the top or bottom face of the resistor element 21, and is disposed at least on the top or bottom face of the resistor element 21. First and second terminals 22 and 23 have a concave groove 25 of the width k which is equivalent to the sum T of the thickness T_1 of the resistor element 21 and the thickness T_2 of the insulating sheet 22, and are provided and electrically connected to both ends of the resistor element 21. The thickness t of these first and second terminals 18 and 19 is thicker than the sum T of the thickness T_1 of the resistor element 21 and the thickness T_2 of the insulating sheet 22; their width m is equivalent to or wider than the width W of the resistor element 21; and their length w is shorter than the length L of the resistor element 21. The first and second terminals 23 and 24 are made of metals such as copper, silver, gold, aluminum, copper nickel, or copper zinc with the same or greater electrical conductivity than that of the resistor element 21.

A manufacturing method of the resistor in the third exemplary embodiment of the present invention as configured above is described next with reference to drawings.

The manufacturing method of the resistor in the third exemplary embodiment is substantially the same as that described for the resistor in the first exemplary embodiment using Fig. 2. A metal sheet or metal strip such as of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy is formed into the resistor element 21 having a predetermined sheet shape and predetermined resistance, calculated from the volume resistivity, section area, and length, through a range of processes including cutting, punching, and pressing. A detail which differs from the first exemplary embodiment is that, after forming the resistor element 21 as described above, the insulating sheet 22 made such as of alumina, glass, glass impregnated

epoxy resin, or paper impregnated phenolic resin having the same two-dimensional size as the resistor element 21 is made such as by dividing, cutting, punching, and pressing, and then attached to the resistor element 21.

Processes and materials for manufacturing the first and second terminals 23 and 24 are the same as those indicated in Fig. 2 (a). However, the thickness t and groove width k of the first and second terminals 23 and 24 differ for the thickness of the insulating sheet 22.

Fourth exemplary embodiment

10 A resistor in a fourth exemplary embodiment of the present invention is described with reference to drawings.

Fig. 6 is a side view of a terminal, a key part, of the resistor in the fourth exemplary embodiment of the present invention seen from an open side.

In Fig. 6, first and second terminals 26 and 27 have a cavity 28 of the same shape as a section face in the width direction of the resistor element 11. The thickness t of these first and second terminals 26 and 27 is thicker than the thickness T of the resistor element 11; their width m is equivalent to or wider than the width W of the resistor element 11; and their length w is shorter than the length L of the resistor element 11. The first and second terminals 26 and 27 are made of metals such as copper, silver, gold, aluminum, copper nickel, or copper zinc with the same or greater electrical conductivity than that of the resistor element 11.

Fifth exemplary embodiment

25 A resistor in a fifth exemplary embodiment of the present invention is described with reference to drawings.

000270 82650550

Fig. 7 (a) is a sectional view, and Fig. 7 (b) is a plan view of the resistor in the fifth exemplary embodiment of the present invention

In Figs. 7 (a) and 7 (b), a resistor element 29 is made such as of a copper-nickel alloy wire, nickel-chromium wire, or copper-manganese-nickel alloy wire.

5 First and second terminals 30 and 31 have a concave groove 32 of the width k which is equivalent to a diameter R of the resistor element 29, and are provided and electrically connected to both ends of the resistor element 29. The thickness t of these first and second terminals 30 and 31 is thicker than the resistor element 29; their width m is equivalent to or greater than the diameter R of the resistor element
10 29; and their length w is shorter than the length L of the resistor element 29. The first and second terminals 30 and 31 are made of metals such as copper, silver, gold, aluminum, copper nickel, or copper zinc with the same or greater electrical conductivity than that of the resistor element 29.

A method for manufacturing the resistor in the fifth exemplary embodiment
15 of the present invention as configured above is described next with reference to drawings.

Figs. 8 (a) to 8 (d) are process charts illustrating the manufacturing method of the resistor in the fifth exemplary embodiment of the present invention.

In Fig. 8 (a), a metal wire made such as of copper, silver, gold, aluminum,
20 copper nickel, or copper zinc which have the same or greater electrical conductivity than that of the resistor element 29 (not illustrated) is ground, cast, forged, pressed, and drawn to form the first and second terminals 30 and 31 having the groove 32 of the width k equivalent to the diameter R of the resistor element 29. The first and second terminals 30 and 31 are formed in a way to achieve the next dimensions:
25 thickness t thicker than that of the resistor element 29, the width m same or greater

than the diameter R of the resistor element 29, and length w shorter than the length L of the resistor element 29.

In Fig. 8 (b), a metal wire such as of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy is cut into the resistor element 29 having a predetermined sheet shape and predetermined resistance, calculated from the volume resistivity, section area, and length.

In Fig. 8 (c), both ends of the resistor element 29 is fitted to the groove 32 of the first and second terminals 30 and 31, and they are thermally pressed in the vertical direction of the terminal (direction of holding the resistor element).

In Fig. 8 (d), a protective film 33 made such as of a film of epoxy resin, polyimide resin, or poly-carbodiimide resin is cut, punched, or pressed into a predetermined shape, placed over and below the resistor element 29 (not illustrated). The protective film 33 is formed on the top, bottom, and side faces of the resistor element 29 by thermal compression bonding or ultrasonic welding to complete the resistor in the fifth exemplary embodiment.

Both ends of the resistor element 29 may be inserted to the groove 32 of the first and second terminals 30 and 31 from the open side or from the side face of the first and second terminals 30 and 31.

For bonding the resistor element 29 and the first and second terminals 30 and 31, a range of methods may be used: (1) welding; (2) brazing after inserting a third conductive metal such as copper, silver, gold, tin, or solder between the resistor element 29 and the first and second terminals 30 and 31; (3) plating and thermal compression bonding the resistor element 29 and first and second terminals 30 and 31; and (4) applying conductive paste to the resistor element 29 and the first and

second terminals 30 and 31, and then thermosetting after fitting the resistor element 29 into the first and second terminals 30 and 31

For adjusting the resistance of the resistor in the fifth exemplary embodiment of the present invention, a through groove may be created on the resistor element 29 or a part of the surface and/or side face of the resistor element 29 may be cut by laser, punching, diamond wheel cutting, grinding, etching, or the like while measuring the resistance between predetermined points or calculating required processing after measuring the resistance. The resistance may also be adjusted or corrected at the time of forming the resistor element 29.

Sixth exemplary embodiment

A resistor in a sixth exemplary embodiment of the present invention is described with reference to drawings.

Fig. 9 (a) is a sectional view, and Fig. 9 (b) is a plan view of the resistor in the sixth exemplary embodiment of the present invention.

In Figs 9 (a) and 9 (b), a resistor element 34 is typically made of a copper-nickel alloy wire, nickel-chromium wire, or copper-manganese-nickel alloy wire bent into a cylindrical coil shape.

First and second terminals 35 and 36 have a concave groove 37 of the width k which is equivalent to the diameter R of the resistor element 34, and are provided and electrically connected to both ends of the resistor element 34. The thickness t of these first and second terminals 35 and 36 is thicker than the total thickness V of the resistor element 34; their width m is equivalent to or wider than the width W of the resistor element 34; and their length w is shorter than the length L of the resistor element 34. The first and second terminals 35 and 36 are made of metals such as

copper, silver, gold, aluminum, copper nickel, or copper zinc with the same or greater electrical conductivity than that of the resistor element 34.

A method for manufacturing the resistor in the sixth exemplary embodiment of the present invention as configured above is described next with reference to
5 drawings.

The manufacturing method of the resistor in the sixth exemplary embodiment is the same as that described for the resistor in the fifth exemplary embodiment using Fig. 8. A metal wire such as of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy is formed into the resistor element 29 having a
10 predetermined wire shape and predetermined resistance, calculated from the volume resistivity, section area, and length, through a range of processes including dividing, cutting, and pressing. A detail which differs from the fifth exemplary embodiment is that, after forming the resistor element 29 as described above, a resistor element wire 29 is bent into a cylindrical coil shape, so as to form the resistor element 34.

15

Seventh exemplary embodiment

A seventh exemplary embodiment of the present invention is described with reference to drawings.

Fig. 10 (a) is a sectional view, and Fig. 10 (b) is a plan view of a resistor in
20 the seventh exemplary embodiment of the present invention.

In Figs. 10 (a) and 10 (b), a resistor element 38, made such as of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy, is bent symmetrically to the left and right in one plane. First and second terminals 39 and 40 have a concave groove 41 of the width k which is equivalent to the diameter R of
25 the resistor element 38, and are provided and electrically connected to both ends of

the resistor element 38. The thickness t of these first and second terminals 39 and 40 is greater than the diameter R of the resistor element 38; their width m is equivalent to or wider than the width W of the resistor element 38; and their length w is shorter than the length L of the resistor element 38. The first and second terminals 39 and 40 are made of metals such as copper, silver, gold, aluminum, copper nickel, or copper zinc with the same or greater electrical conductivity than that of the resistor element 38.

A manufacturing method of the resistor in the seventh exemplary embodiment of the present invention as configured above is described next with reference to drawings.

The manufacturing method of the resistor in the seventh exemplary embodiment is the same as that described for the resistor in the fifth exemplary embodiment using Fig. 8. A metal wire such as of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy is formed into the resistor element 29 having a predetermined wire shape and predetermined resistance, calculated from the volume resistivity, section area, and length, through a range of processes including dividing, cutting, and pressing. A detail which differs from the fifth exemplary embodiment is that, after forming the resistor element 29 as described above, a resistor element wire 9 is bent symmetrically to the left and right in one plane in accordance with dimensions required for the resistor, so as to form the resistor element 38.

Eighth exemplary embodiment

A resistor in an eighth exemplary embodiment of the present invention is described below with reference to drawings.

Fig. 11 (a) is a sectional view, Fig. 11 (b) is a plan view, and Fig. 11 (c) is a sectional view of a terminal, a key part, of the resistor in the eighth exemplary embodiment of the present invention.

In Figs. 11 (a) to 11 (c), first and second resistor elements 42 and 43 are made typically of a copper-nickel alloy wire, nickel-chromium wire, or copper-manganese-nickel alloy wire. First and second terminals 44 and 45 have a concave groove 46 of the width k which is equivalent to the diameter R of the resistor elements 42 and 43, and are provided and electrically connected to both ends of the resistor elements 42 and 43. The thickness t of these first and second terminals 44 and 45 is thicker than that of the resistor elements 42 and 43; their width m is equivalent to or wider than the width W of the resistor elements 42 and 43; and their length w is shorter than the length L of the resistor elements 42 and 43. The first and second terminals 44 and 45 are made of metals such as copper, silver, gold, aluminum, copper nickel, or copper zinc with the same or greater electrical conductivity than that of the resistor elements 42 and 43.

A method for manufacturing of the resistor in the eighth exemplary embodiment of the present invention as configured above is described next with reference to drawings.

The manufacturing method of the resistor in the eighth exemplary embodiment is the same as that described for the resistor in the fifth exemplary embodiment using Fig. 8. A metal wire such as of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy is formed into a plurality of resistor elements 42 and 43 having a predetermined wire shape and predetermined resistance, calculated from the volume resistivity, section area, and length, through a range of processes including cutting, punching, and pressing. A detail which differs

from the fifth exemplary embodiment is that, after forming the resistor elements 42 and 43 as described above, these resistor elements 42 and 43 are connected to the first and second terminals 44 and 45 in a way that the resistor elements 42 and 43 do not directly and electrically contact each other.

5 Fig. 12 is a side view of a terminal in another example of the resistor in the eighth exemplary embodiment of the present invention.

In Fig. 12, first and second cavities 47 and 48 have a section shape equivalent to the first and second resistor elements 42 and 43 and are formed respectively on the first and second terminals 44 and 45 instead of the concave
10 groove 46 of the width k equivalent to the diameter R of the resistor elements 42 and 43 shown in Fig. 11.

Ninth exemplary embodiment

A resistor in a ninth exemplary embodiment of the present invention is
15 described below with reference to drawings.

Fig. 13 (a) is a sectional view, and Fig. 13 (b) is a plan view of the resistor in the ninth exemplary embodiment of the present invention.

In Figs. 13 (a) and 13 (b), a resistor element 49 is made typically a sheet or strip of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel
20 alloy. First and second terminals 50 and 51 have a concave groove 52 of the width k which is equivalent to the total thickness T of the resistor element 49, and are provided and electrically connected to both ends of the resistor element 49. The thickness t of these first and second terminals 50 and 51 is thicker than the total thickness T of the resistor element 49; their width m is equivalent to or wider than the
25 width W of the resistor element 49; and their length w is shorter than the length L of

000270" 9260550

the resistor element 49. The first and second terminals 50 and 51 are made of metals such as copper, silver, gold, aluminum, copper nickel, or copper zinc with the same or greater electrical conductivity than that of the resistor element 49. A protective film 53, made such as of epoxy resin, polyimide resin, or poly-carbodiimide resin is formed on the resistor element 49 at an area not connected to the first and second terminals 50 and 51.

A manufacturing method of the resistor in the ninth exemplary embodiment of the present invention as configured above is described next with reference to drawings.

The manufacturing method of the resistor in the ninth exemplary embodiment is basically the same as that described for the resistor in the first exemplary embodiment using Fig. 2. More specifically, a film of epoxy resin, polyimide resin, poly-carbodiimide resin, or the like is disposed to vertically sandwich the resistor element 49, and the protective film 53 is formed on the top, bottom, and side faces of the resistor element 49 by thermal compression bonding or ultrasonic welding, regardless of the shape of the resistor element, to complete the resistor in the ninth exemplary embodiment of the present invention.

Tenth exemplary embodiment

A resistor in a tenth exemplary embodiment of the present invention is described below with reference to drawings.

Fig. 14 (a) is a sectional view, Fig. 14 (b) is a plan view, and Fig. 14 8c) is a sectional view of a terminal, cut in a width m direction, of the resistor in the tenth exemplary embodiment of the present invention.

In Figs. 14 (a) to 14 (c), a resistor element 54 is made typically of a shape or a strip of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy. First and second terminals 55 and 56 have a concave groove 57 of the width k which is equivalent to the total thickness T of the resistor element 54, and are provided and electrically connected to both ends of the resistor element 54. The thickness t of these first and second terminals 55 and 56 is thicker than the total thickness T of the resistor element 54; their width m is equivalent to or wider than the width W of the resistor element 54; and their length w is shorter than the length L of the resistor element 54. The first and second terminals 55 and 56 are made of metals such as copper, silver, gold, aluminum, copper nickel, or copper zinc with the same or greater electrical conductivity than that of the resistor element 54. A protective film 58, made such as of epoxy resin, polyimide resin, or poly-carbodiimide resin, is formed on the resistor element 54 at an area not connected to the first and second terminals 55 and 56 to achieve the same dimensions as the width m and thickness t of the first and second terminals 55 and 56.

A method for manufacturing the resistor in the tenth exemplary embodiment of the present invention as configured above is basically the same as that described for the resistor in the first exemplary embodiment using Fig. 2. More specifically, a film of epoxy resin, polyimide resin, poly-carbodiimide resin, or the like is disposed to vertically sandwich the resistor element 54, and the protective film 58 is formed on the top, bottom, and side faces of the resistor element 54 by thermo compression bonding or ultrasonic welding, regardless of the shape of the resistor element, to complete the resistor in the tenth exemplary embodiment of the present invention.

A detail which differs from the ninth exemplary embodiment of the present invention is a formation area of the protective film 58. The protective film 58 is

formed on the resistor element 54 to level with the width m and thickness t of the first and second terminals 55 and 56. This can be achieved by making the thickness of a film of epoxy resin, polyimide resin, or poly-carbodiimide resin thicker than the difference between the top surface level of the resistor element 54 and top surface level of the first and second terminals 55 and 56, and difference between the lower surface level of the resistor element 54 and lower surface level of the first and second terminals 55 and 56; and pressing the film to the same level as the top and bottom faces of the first and second terminals 55 and 56.

Eleventh exemplary embodiment

A resistor in an eleventh exemplary embodiment of the present invention is described below with reference to drawings.

Fig. 15 (a) is a sectional view, and Fig. 15 (b) is a plan view of the resistor in the eleventh exemplary embodiment of the present invention.

In Figs. 15 (a) and 15 (b), a resistor element 59 is made typically of a sheet or strip of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy. First and second terminals 60 and 61 have an L shape section face, and are provided and electrically connected to both ends of the resistor element 59. The thickness y of these first and second terminals 60 and 61 underneath the resistor element 59 is greater than the thickness x contacting the end face of the resistor element 59. The first and second terminals 60 and 61 are made of metals such as copper, silver, gold, aluminum, copper nickel, or copper zinc with the same or greater electrical conductivity than that of the resistor element 59.

A method for manufacturing the resistor in the eleventh exemplary embodiment of the present invention as configured is basically the same as that

described for the resistor in the first exemplary embodiment using Fig. 2. However, in the eleventh exemplary embodiment, the first and second terminals 60 and 61 having the L-shape section face are formed instead of the shape of the first and second terminals illustrated in Fig. 2 (a). In a process corresponding to Fig. 2 (c), the resistor element 59 is placed on the first and second terminals 60 and 61. For bonding the resistor element 59 and the first and second terminals 60 and 61, a range of methods may be used: (1) welding; (2) brazing after inserting a third conductive metal such as copper, silver, gold, tin, and solder between the resistor element 59 and the first and second terminals 60 and 61; and (3) applying conductive paste to the resistor element 59 and the first and second terminals 60 and 61, and then thermosetting after fitting the resistor element 59 into the first and second terminals 60 and 61.

Twelfth exemplary embodiment

A resistor in a twelfth exemplary embodiment of the present invention is described below with reference to drawings.

Fig. 16 is a sectional view of the resistor in the twelfth exemplary embodiment of the present invention.

In Fig. 16, a resistor element 64 is made typically of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy. An insulating sheet 65, made such as of alumina, glass, glass impregnated epoxy resin, or paper impregnated phenolic resin, is attached to the top face of the resistor element 64. First and second terminals 66 and 67 have an L-shape section face, and are provided and electrically connected to both ends of the resistor element 64. The first and second terminals 66 and 67 are made of metals such as copper, silver, gold, aluminum,

copper nickel, or copper zinc with the same or greater electrical conductivity than that of the resistor element 64. The insulating sheet 65 may also be attached to the bottom face of the resistor element 64.

A method for manufacturing the resistor in the twelfth exemplary embodiment as configured above is basically the same as that described for the resistor in the eleventh exemplary embodiment. However, in the twelfth exemplary embodiment, the first and second terminals 66 and 67 having the L-shape section face are formed instead of the shape described in Fig. 2 (a). In a process corresponding to Fig. 2 (b), a metal sheet or metal strip such as of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy is formed into the resistor element 64 having a predetermined sheet shape and predetermined resistance, calculated from the volume resistivity, section area, and length, through a range of processes including cutting, punching, and pressing. Then, the insulating sheet 65, made such as of alumina, glass, glass impregnated epoxy resin, or paper impregnated phenolic resin, with the same two-dimensional size as the resistor element 64, is obtained by dividing, cutting, punching, or pressing, and the resistor element 64 and insulating sheet 65 are pasted. In a process corresponding to Fig. 2 (c), the resistor element 64 is placed on the first and second terminals 60 and 61. For bonding the resistor element 64 and the first and second terminals 66 and 67, a range of methods may be used: (1) welding; (2) brazing after inserting a third conductive metal such as copper, silver, gold, tin, and solder between the resistor element 64 and the first and second terminals 66 and 67; and (3) applying conductive paste to the resistor element 64 and the first and second terminals 66 and 67, and then thermosetting after fitting the resistor element 64 into the first and second terminals 66 and 67.

Thirteenth exemplary embodiment

A resistor in a thirteenth exemplary embodiment of the present invention is described below with reference to drawings.

Fig. 17 is a sectional view of the resistor in the thirteenth exemplary embodiment of the present invention.

In Fig. 17, a resistor element 68, made of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy has a shape that both ends are thicker than a central portion, and there is a step between the central portion and ends (its length-wise section face show an H shape). Steps 69 and 70 are provided at both ends 71 and 72 which are thicker than a central portion 73 of the resistor element 68. First and second terminals 74 and 75 are electrically connected to both ends of the resistor element 68, and their section face has a one-side open shape. Inside the first and second terminals 74 and 75 is wider than openings 76 and 77. The first and second terminals 74 and 75 are made of metals such as copper, silver, gold, aluminum, copper nickel or copper zinc which have the same or greater electrical conductivity than that of the resistor element 68.

In Fig. 17, the steps 69 and 70 and the openings 76 and 77 are bent in the thickness direction for preventing detachment, however, the direction is not limited. For example, they may be bent vertical against the thickness direction. The number of steps and bendings are also not limited.

A method for manufacturing the resistor in the thirteenth exemplary embodiment of the present invention as configured above is basically the same as that described for the resistor in the first exemplary embodiment using Fig. 2. A detail which differs is the shape of the material. In a process corresponding to Fig. 2 (a), inside of the first and second terminals 74 and 75 is broader than their openings 76

and 77. In a process corresponding to Fig. 2 (b), steps 69 and 70 thicker than the central portion 73 are provided at both ends 71 and 72 of the resistor element 68 in accordance with the shape of the groove of the first and second terminals 74 and 75.

Fourteenth exemplary embodiment

A resistor in a fourteenth exemplary embodiment of the present invention is described below with reference to drawings.

Fig. 18 is a sectional view of the resistor in the fourteenth exemplary embodiment of the present invention.

In Fig. 18, an insulating substrate 79 is a sheet of a glass impregnated epoxy resin substrate, paper impregnated phenolic resin substrate, or the like. First and second terminals 80 and 81 are formed on both ends of the insulating substrate 79 for electrically connecting the top and bottom faces of the insulating substrate 79, and are made of metals such as copper, silver, gold, aluminum, copper nickel, or copper zinc with the same or greater electrical conductivity than that of a resistor element 78. A metal layer 82 such as of solder is formed on the top face of the first and second terminals 80 and 81. The resistor element 78 made such as of a sheet of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy is formed on the metal layer 82 in a way to electrically connect the metal layer 82 on the first terminal 80 and the metal layer 82 on the second terminal 81.

In Fig. 18, the top and bottom faces of the insulating substrate 79 are electrically connected by the first and second terminals 80 and 81 on both ends of the insulating substrate 79. This may also be achieved by providing the electrodes which vertically penetrate through the insulating substrate 79.

A method for manufacturing the resistor in the fourteenth exemplary embodiment of the present invention is described next with reference to drawings.

Figs. 19 (a) to 19 (c) are process charts illustrating the manufacturing method of the resistor in the fourteenth exemplary embodiment of the present invention.

5 In Fig. 19 (a), a strip of metal foil pattern typically made of copper, silver, or gold having the same or greater electrical conductivity than that of the resistor element 78 is formed on the top, bottom, and side faces of the insulating substrate 79 made typically of a glass impregnated epoxy resin substrate or paper impregnated phenolic resin substrate. Then, the metal foil pattern is exposed to the light and
10 etched to form the first and second terminals 80 and 81 with a predetermined shape.

In Fig. 19 (b), solder paste 82 is screen printed on the top face of the first and second terminals 80 and 81.

In Fig. 19 (c), a metal sheet made typically of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy is formed into the resistor element
15 78 having a predetermined sheet shape and predetermined resistance, calculated from the volume resistivity, section area, and length, through a range of processes including cutting, punching, and pressing. Both ends of the resistor element 78 are placed on the top face of the solder paste 82, and firmly bonded by the reflow process to complete the resistor in the fourteenth exemplary embodiment of the present
20 invention.

In the fourteenth exemplary embodiment of the present invention, the resistor element 78 and the first and second terminals 80 and 81 are bonded by soldering the solder paste 82. This may also be achieved through other methods such as: (1)
25 solder between the resistor element 78 and the first and second terminals 80 and 81;

and (2) plating and thermal compression bonding the resistor element 78 and first and second terminals 80 and 81.

For adjusting the resistance of the resistor element in the fourteenth exemplary embodiment of the present invention, a through groove may be created on the resistor element 78 or a part of the surface and/or side of the resistor element 78 may be cut by laser, punching, diamond wheel cutting, grinding, etching, and so on while measuring the resistance between predetermined points or calculating required processing after measuring the resistance. The resistance may also be adjusted or corrected at the time of forming the resistor element 78.

Fifteenth exemplary embodiment

A resistor in a fifteenth exemplary embodiment of the present invention is described below with reference to drawings.

Fig. 20 (a) is a sectional view, Fig. 20 (b) is a plan view of the surface, and Fig. 20 (c) is a plan view of the rear face of the resistor in the fifteenth exemplary embodiment of the present invention.

In Figs. 20 (a) to 20 (c), a resistor element 83 is made such as of a sheet of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy. An insulating substrate 83 is a sheet of a glass impregnated epoxy resin substrate, paper impregnated phenolic resin substrate, or the like. First, second, third, and fourth terminals 85, 86, 87, and 88 are disposed at four corners of the insulating substrate 84, in a way to electrically connect top and bottom faces of the insulating substrate 84, and are made of metals such as copper, silver, gold, aluminum, copper nickel, or copper zinc with the same or greater electrical conductivity than that of the resistor element 83. The resistor element 83 is electrically connected to the surface of the

first, second, third, fourth terminals 85, 86, 87, and 88 through a metal layer 89 on their top faces.

In Fig. 20, the first, second, third, fourth terminals 85, 86, 87, and 88 are formed at four corners of the insulated substrate 84 so as to electrically connect the top and bottom faces of the insulated substrate 84. This may also be achieved by providing the electrodes which vertically penetrate through the insulating substrate 79.

A method for manufacturing the resistor in the fifteenth exemplary embodiment of the present invention is the same as that described using Fig. 19. The difference is that four terminals are formed in the fifteenth exemplary embodiment, while two terminals are formed in the fourteenth exemplary embodiment.

Sixteenth exemplary embodiment

A resistor in a sixteenth exemplary embodiment of the present invention is described below with reference to drawings.

Fig. 21 (a) is a sectional view, and Fig. 21 (b) is a plan view of the resistor in the sixteenth exemplary embodiment of the present invention.

In Figs. 21 (a) and 21 (b), a resistor element 90 is made such as of a sheet of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy. Rectangular parallelepiped first, second, third, and fourth terminals 91, 92, 93, and 94 are electrically connected respectively at the top and bottom faces of both ends of the resistor element 90.

A method for manufacturing the resistor in the sixteenth exemplary embodiment as configured above is basically the same as that described for the

000270 825555

resistor in the first exemplary embodiment using Fig. 2. In a process corresponding to Fig. 2 (a), four rectangular parallelepiped terminals are formed. In a process corresponding to Fig. 2 (c), the first and third terminals 91 and 93 are bonded to the top face of both ends of the resistor element 90, using processes such as: (1) welding after disposing the first and third terminals 91 and 93 on the top face of both ends of the resistor element 90; (2) inserting a third conductive metals such as copper, silver, gold, tin, or solder between the resistor element and terminals, disposing the first and third terminals 91 and 93 on the top face of both ends of the resistor element 90, and brazing; or (3) applying conductive paste to the resistor element 90 and the first and third terminals 91 and 93, disposing the first and third terminals 91 and 93 on the top face of both ends of the resistor element 90, and thermosetting. Then, the resistor element 90 is turned over to bond the second and fourth terminals 92 and 94 on the bottom face of both ends of the resistor element 90 using the aforementioned processes. The above operation may be implemented at once to bond the first, second, third, and fourth terminals 91, 92, 93, and 94 to the resistor element 90.

Fig. 22 is a sectional view of another example of the resistor in the sixteenth exemplary embodiment of the present invention.

A detail which differs from Fig. 21 in fig. 22 is that the first and second terminals 91 and 92, and the third and fourth terminals 93 and 94 are electrically connected, and each pair of terminals looks like a single terminal.

Accordingly, the manufacturing method of the example shown in Fig. 22 is that (1) welding after disposing the first and third terminals 91 and 93 on the top face of both ends of the resistor element 90; (2) inserting a third conductive metals such as copper, silver, gold, tin, or solder between the resistor element and terminals, disposing the first and third terminals 91 and 93 on the top face of both ends of the

resistor element 90, and brazing; or (3) applying conductive paste to the resistor element 90 and the first and third terminals 91 and 93, disposing the first and third terminals 91 and 93 on the top face of both ends of the resistor element 90, and thermosetting. When the resistor element 90 is turned over, after bonding the first and third terminals 91 and 93 on the top face of both ends of the resistor element 90, to bond the second and fourth terminals 92 and 94 on the bottom face of both ends of the resistor element 90, the first and second terminals 91 and 92, and the third and fourth terminals 93 and 94 are simultaneously connected.

Seventeenth exemplary embodiment

A resistor in a seventeenth exemplary embodiment of the present invention is described below with reference to drawings.

Fig. 23 is a sectional view of the resistor in the seventeenth exemplary embodiment of the present invention.

In Fig. 23, a resistor element 95, made typically of a sheet of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy has first and second notches 96 and 97 provided near both ends. These first and second notches 96 and 97 in the resistor element 95 are created as a widthwise slit on the resistor element 95. First and second terminals 98 and 99 are made of metals such as copper, silver, gold, aluminum, copper nickel, or copper zinc having the same or greater electrical conductivity than that of the resistor element 95.

First and second protrusions 100 and 101 on the first and second terminals 98 and 99 have the same or smaller size than that of the first and second notches 96 and 97, and they are provided as a widthwise slit on the first and second terminals 98 and

99.

The first and second terminals 98 and 99 are disposed at both ends of the resistor element 95. The first notch 96 on the resistor element 95, and the first protrusion 100 on the first terminal 98, and the second notch 97 on the resistor element 95 and second protrusion 101 on the second terminal 99 are mechanically connected respectively. In addition, the resistor element 95 and the first and second terminals 98 and 99 are electrically connected.

A method for manufacturing the resistor in the seventeenth exemplary embodiment of the present invention is described next with reference to drawing.

The manufacturing method of the resistor in the seventeenth exemplary embodiment of the present invention is basically the same as that described for the resistor in the first exemplary embodiment using Fig. 2. However, the shape of the first and second terminals differ from that described in Fig. 2 (a). The notches 96 and 97 are also created on the resistor element 95, which is different from the resistor element described in Fig. 2 (b). The first and second notches 96 and 97 are created such as by cutting and pressing after forming the resistor element 95 with a predetermined sheet shape and predetermined resistance. In a process corresponding to Fig. 2 (c), as shown in Fig. 23, the resistor element 95 is placed on the first and second terminals 98 and 99 in a way that the first notch 96 on the resistor element 95 fits with the first protrusion 100 on the first terminal 98, and the second notch 97 on the resistor element 95 fits with the second protrusion 101 on the second terminal 99. Then, the resistor element 95 and the first and second terminals 98 and 99 are bonded and connected using the next methods: (1) welding; (2) brazing after inserting a third conductive metal such as copper, silver, gold, tin, and solder between the resistor element 95 and the first and second terminals 98 and 99; and (3) applying conductive paste between the resistor element 95 and the first and second

terminals 98 and 99, and thermosetting after fitting the resistor element 95 into the first and second terminals 98 and 99.

Eighteenth exemplary embodiment

5 A resistor in an eighteenth exemplary embodiment of the present invention is described below with reference to drawings.

Fig. 24 (a) is a sectional view, and Fig. 24 (b) is a plan view of the resistor in the eighteenth exemplary embodiment of the present invention.

As shown in Fig. 24, a resistor element 102, made such as of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy has first and second through holes 103 and 104. First and second terminals 105 and 106 have first and second protrusions 107 and 108 which can be inserted to the first and second through holes 103 and 104, and are made of metals such as copper, silver, gold, aluminum, copper nickel, or copper zinc having the same or greater electrical conductivity than that of the resistor element 102.

15 The first and second terminals 105 and 106 are disposed at both ends of the resistor element 102. The first through hole 103 on the resistor element 102, and the first protrusion 107 on the first terminal 105, and the second through hole 104 on the resistor element 102 and second protrusion 108 on the second terminal 106 are mechanically connected respectively. In addition, the resistor element 102 and the first and second terminals 105 and 106 are electrically connected.

20 A manufacturing method of the resistor in the eighteenth exemplary embodiment of the present invention as configured above is described next with reference to drawings.

Figs. 25 (a) to 25 (e) are process charts illustrating the manufacturing method of the resistor in the eighteenth exemplary embodiment of the present invention.

As shown in Fig. 25 (a), first and second terminals 105 and 106 have first and second protrusions 107 and 108, and are made of metal sheet or metal strip such as of copper, silver, gold, aluminum, copper nickel, or copper zinc with the same or greater electrical conductivity than that of the resistor element 102 using processes such as cutting, casting, forging, pressing, and drawing.

In Fig. 25 (b), a metal sheet or metal strip such as of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy is formed into the resistor element 102 having a predetermined sheet shape and predetermined resistance, calculated from the volume resistivity, section area, and length, through a range of processes including cutting, punching, and pressing.

In Fig. 25 (c), the first and second through holes 103 and 104 are created in both ends of the resistor element 102 using processes such as punching, cutting, and laser.

In Fig. 25 (d), the first protrusion 107 on the first terminal 105 is inserted into the first through hole 103 on the resistor element 102, and the second protrusion 108 on the second terminal 106 is inserted into the second through hole 104 on the resistor element 102.

In Fig. 25 (e), the first and second terminals 105 and 106 are bent along the circumference of the resistor element 102 by pressing to sandwich the resistor element 102 in the thickness direction.

The first and second terminals 105 and 106 may not necessary have the shape shown in Figs. 25 (a) to 25 (e). They may just have an opening sufficient for

inserting the resistor element 102, and then caulked after inserting the resistor element 102 at both ends.

The resistor element 102 and the first and second terminals 105 and 106 may be bonded and connected using the next methods: (1) welding; (2) brazing after
 5 inserting a third conductive metal such as copper, silver, gold, tin, and solder between the resistor element 102 and the first and second terminals 105 and 106; and (3) applying conductive paste between the resistor element 102 and the first and second terminals 105 and 106, and thermosetting.

For adjusting the resistance of the resistor in the eighteenth exemplary
 10 embodiment of the present invention, a through groove may be created on the resistor element 102 or a part of the surface and/or side of the resistor element 102 may be cut by laser, punching, diamond wheel cutting, grinding, etching, and so on while measuring the resistance between predetermined points or calculating the required processing after measuring the resistance. The resistance may also be adjusted or
 15 corrected at the time of forming the resistor element 102.

In the first exemplary embodiment as described above, the groove 14 of the first and second terminals 12 and 13 is fitted to both ends of the resistor element 11, and then the first and second terminals 2 and 13 are thermally pressed in the vertical
 20 direction (to hold the resistor element 11) so that the first and second terminals 12 and 13 are disposed at the top and bottom faces of the resistor element 11. As a result, it has an effect that the resulting resistor may be mounted in either way, regardless of the surface and rear face of the resistor.

In the second exemplary embodiment as described above, a metal sheet is
 25 corrugated to the thickness direction to form the resistor element 17. An upper limit

of the resistance of the resistor may be increased by bending the resistor element 17 in such a way that the length L of the resistor element 17 becomes longer in the length direction. On the other hand, a lower limit of the resistance of this resistor may be reduced by bending the resistor element 17 in a way that its width W becomes longer.

The second exemplary embodiment of the present invention also has the first and second terminals 18 and 19 which have the groove 20 of the width k equivalent to the thickness T of the resistor element 17. The thickness t of the terminals is thicker than the total thickness V of the resistor element 17, their width m is equivalent to or longer than the width W , and their length w is shorter than the length L of the resistor element 17. This enables to make the resistance of the first and second terminals 18 and 19 smaller than that of the resistor element 17 by the shape, and thus reduces the proportion of the resistance of the first and second terminals 18 and 19 in the entire resistor. This enables to reduce fluctuation in the resistance which is dependant of a resistance measuring terminal on a contact point. Furthermore, since a clearance is provided between the resistor element 17 and a circuit board, thermal damage to a mounting circuit board due to self heat generation of the resistor element 17 is preventable.

The third exemplary embodiment of the present invention comprises the metal sheet resistor element 21, insulating sheet 22 disposed at least on one of the top and bottom faces of the resistor element 21, and the first and second terminals 23 and 24 electrically connected to the resistor element 21. The first and second terminals 23 and 24 have the groove 25 of the width k equivalent to the sum T of the thickness T_1 of the resistor element 21 and the thickness T_2 of the insulating sheet 22, and are electrically connected to the resistor element 21. The insulating sheet 22 supports

or reinforces the resistor element 21, and improves mechanical strength, thus preventing changes in characteristics by deformation.

Also in the third exemplary embodiment, the first and second terminals 23 and 24 have the groove 25 of the width k equivalent to the sum T of the thickness T_1 of the resistor element 21 and the thickness T_2 of the insulating sheet 22. The thickness t of the first and second terminals 23 and 24 is also thicker than the sum T of the thickness T_1 of the resistor element 21 and the thickness T_2 of the insulating sheet 22, their width m is equivalent to or wider than the width W of the resistor element 21, and their length w is shorter than the length L of the resistor element 21. This shape enables to make the resistance of the first and second terminals 23 and 24 smaller than that of the resistor element 21, and thus reduces the proportion of the resistance of the first and second terminals 23 and 24 in the entire resistor. Accordingly, fluctuation in the resistance dependant of a resistance measuring terminal on a contact point may be reduced. Furthermore, since a clearance is provided between the resistor element 17 and a substrate, thermal damage to a mounting substrate due to self heat generation of the resistor element 17 is preventable.

The fifth exemplary embodiment of the present invention comprises the metal wire resistor element 29, the concave groove 32 covering both ends of the resistor element 29, and first and second metal terminals 30 and 31 electrically connected to the resistor element 29. The wire resistor element 29 which has the diameter greater than thickness than that of the sheet resistor element enables to obtain the larger resistance than that obtainable with the sheet resistor element. Its mechanical strength can also be reinforced to improve the bending strength of the resistor.

The seventh exemplary embodiment of the present invention comprises the metal wire resistor element 38 bent symmetrically to the left and right in one plane, concave groove 41 covering both ends of the resistor element 38, and first and second metal terminals 39 and 40 electrically connected to the resistor element 38. Since the metal wire configuring the resistor element 38 is bent symmetrically to the left and right in one plane, the current direction alternates. This enables to cancel the magnetic field generated, and thus reduces magnetic interference of the resistor.

The eleventh exemplary embodiment of the present invention comprises the metal sheet resistor element 59, and first and second metal terminals 60 and 61 having an L-shape section face disposed at both ends of the resistor element 59 and electrically connected to the resistor element 59. An inner wall of the L-shape first

The eleventh exemplary embodiment of the present invention comprises the metal sheet resistor element 59, and first and second metal terminals 60 and 61 having an L-shape section face disposed at both ends of the resistor element 59 and electrically connected to the resistor element 59. An inner wall of the L-shape first

and second terminals 60 and 61 acts as a reference for positioning the first and second terminals 60 and 61 to both ends of the resistor element 59. This enables to improve the accuracy of connecting position of the first and second terminals 60 and 61 and the resistor element 59, reducing deviation in resistance.

5 Also in the eleventh exemplary embodiment of the present invention, the thickness y of a portion of the first and second terminals 60 and 61 underneath the resistor element 59 is made thicker than the thickness x of a portion contacting end faces of the resistor element 59, improving heat radiation performance.

10 The twelfth exemplary embodiment of the present invention comprises the metal sheet resistor element 64, insulating sheet 65 pasted on at least one of the top and bottom faces of the resistor element 64, and the first and second metal terminals 66 and 67 having an L-shape section face disposed at both ends of the resistor element 64 and electrically connected to the resistor element 64. The insulating sheet 65 supports or reinforces the resistor element 64. This enables to improve the
15 mechanical strength and prevent changes in characteristics due to deformation.

The thirteenth exemplary embodiment of the present invention comprises the resistor element 68 provided with the steps 69 and 70 between the central portion 73 and both ends 71 and 72 by making the both ends 71 and 72 thicker than the central portion 73, and the first and second metal terminals 74 and 75 disposed at both ends
20 of the resistor element 68. The first and second metal terminals 74 and 75 have a one-end open section face, and their inside is broader than their opening. The steps 69 and 70 of the resistor element 68 are at least electrically connected to the inside of the opening of the first and second terminals 74 and 75. This mechanical connection of the inside of the opening of the first and second terminals 74 and 75
25 and the steps 69 and 70 of the resistor element 68 enables to improve the accuracy of

bonding position and reliability of bonding between the first and second terminals 74 and 75 and the resistor element 68.

5 The fourteenth exemplary embodiment of the present invention comprises the metal sheet resistor element 78, insulating substrate 79, and the first and second metal terminals 80 and 81 formed to electrically connect the top and bottom faces of the insulating substrate 79 at both ends. The resistor element 78 and the first and second metal terminals 80 and 81 disposed on the top face of the insulating substrate 79 are also electrically connected. This improves the accuracy of formation position and dimensions of the first and second terminals 80 and 81 to control a connection area of the first and second terminals 80 and 81 and the resistor element 78, reducing dispersion in resistance of the resistor.

10 The fifteenth exemplary embodiment of the present invention comprises the metal sheet resistor element 83, insulating substrate 84, and four metal terminals 85, 86, 87, and 88 formed to electrically connect the top and bottom faces of the insulating substrate 84. The resistor element 83 and the four metal terminals 85, 86, 87, and 88 disposed on the top face of the insulating substrate 84 are also electrically connected. This achieves a four-terminal resistor, improving the accuracy of current detection.

15 The sixteenth exemplary embodiment of the present invention comprises the metal resistor element 90 and four metal terminals 91, 92, 93, and 94. Each of the terminals 91, 92, 93, and 94 is disposed on and electrically connected to the top and bottom faces of both ends of the resistor element 90. The four metal terminals 91, 92, 93, and 94 are thus symmetrically disposed, with the resistor element 90 in the center, to the thickness direction of the resistor element 90. This eliminates the directivity of the surface and rear face of the resistor.

20

25

The sixteenth exemplary embodiment, as shown in Fig. 22, also has the terminals 91, 92, 93, and 94 disposed on the top and bottom faces of both ends of the resistor element 90, and these terminals are electrically connected to each other. These four terminals 91, 92, 93, and 94 are thus disposed symmetrically, with the resistor element 90 in the center, to the thickness direction of the resistor element 90. This eliminates the directivity of the surface and rear face of the resistor, further increasing the terminal volume for improving radiating performance.

The seventeenth exemplary embodiment of the present invention comprises the metal resistor element 95 having the first and second notches 96 and 97 near its both ends, and the first and second metal terminals 98 and 99 disposed at both ends of the resistor element 95. The first and second terminal 98 and 99 have the first and second protrusions 100 and 101 corresponding to the first and second notches 96 and 97. The resistor element 95 and the first and second terminals 98 and 99 are at least electrically connected through the first and second protrusions 100 and 101, and the first and second notches 96 and 97. The mechanical connection of the protrusions 100 and 101 and the notches 96 and 97 improves the accuracy of position and resistance, and reliability of bonding between the resistor element 95 and the first and second terminals 98 and 99.

The eighteenth exemplary embodiment of the present invention comprises the metal resistor element 102 having two or more first and second through holes 103 and 104, and the first and second metal terminals 105 and 106 disposed at both ends of the resistor element 102. The first and second terminals 105 and 106 have one or more first and second protrusions 107 and 108 with the same shape as the through holes 103 and 104. At least one of the protrusions 107 and 108 of the terminals 105 and 106 is inserted into at least one of the through holes 103 and 104 of the resistor

element 102, and at least one face of the terminals 105 and 106 is electrically connected to the resistor element 102. The mechanical connection of the protrusions 107 and 108 and the through holes 103 and 104 improves the accuracy of position and resistance, and reliability of bonding between the resistor element 102 and the first and second terminals 105 and 106.

The manufacturing method of the resistor in the fourteenth exemplary embodiment comprises the steps of forming the first and second terminals 80 and 81 with a metal foil pattern with a predetermined shape whose top and bottom faces are electrically connected to a part of the top, side, and bottom faces of the insulated substrate 79. This enables to use the thin film formation process such as light exposure for the metal foil pattern, and thus the accuracy of shape and formation position can be improved. Accordingly, dispersion in the resistance at terminals and a connected portion between the terminals and resistor element can be reduced.

Nineteenth exemplary embodiment

A resistor in a nineteenth exemplary embodiment of the present invention is described below with reference to the drawings.

Fig. 26 (a) is a sectional view, Fig. 26 (b) is a plan view, and Fig. 26 (c) is a sectional view taken along Line A-A in Fig. 26 (a) of the resistor in the nineteenth exemplary embodiment of the present invention.

In Figs. 26 (a) to 26 (c), a resistor element 111 is typically made of a sheet of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy or combination thereof. First and second concaved terminals 112 and 113 have a concave groove 114 of a width k equivalent to the thickness T of the resistor element 111. The entire surface of the first and second terminals 112 and 113 are coated with a low melting point metal 115 (hereinafter metal 115).

5
10
15
20

A manufacturing method of the resistor in the nineteenth exemplary embodiment of the present invention as configured above is described next with reference to drawings.

Figs. 27 (a) to 27 (b) are process charts illustrating the manufacturing method of the resistor in the nineteenth exemplary embodiment of the present invention.

In Fig. 27 (a), first and second terminals 112 and 113 are made of metals such as copper, silver, gold, or aluminum with greater electrical conductivity than that of the resistor element 111 using processes such as cutting, casting, forging, pressing, and drawing. The first and second terminals 112 and 113 have a groove 114 of a width k which is equivalent to or greater than the thickness T of the resistor element 111. The thickness t of these first and second terminals 112 and 113 is greater than the thickness T of the resistor element 111; their width m is equivalent to or wider than the width W of the resistor element 111; and their length w is shorter than the length L of the resistor element 111.

In Fig. 27 (b), the metal 115 is formed on the entire face of the first and second terminals 112 and 113, typically by barrel plating.

In a process shown in Fig. 27 (c), a metal sheet made of copper-nickel alloy, nickel-chromium alloy, or copper-manganese-nickel alloy is formed into the resistor element 111 by a range of processes including cutting, punching, and pressing. The resistor element has a predetermined sheet shape and predetermined resistance, calculated from the volume resistivity, section area, and length.

In Fig. 27 (d), the first and second terminals 112 and 113 are coated with the metal 115 and disposed to both ends of the resistor element 11 through the groove 114, and set on a die for cold forging of the first and second terminals 112 and 113.

Then, a work piece is loaded to and unloaded from an oven held at the temperature above the melting point of the metal 115 (not illustrated) to electrically connect the first and second terminals 112 or 113 and resistor element 111 through the metal 115.

5 Lastly, in Fig. 27(e), the insulated protective film 116, made of a film of epoxy resin, polyimide resin, or poly-carbodiimide resin, is cut into a predetermined shape using processes such as cutting, punching, and pressing, and disposed on the top and bottom faces of the resistor element 111 (not illustrated). The insulated protective film 116 is thermal compression bonded on the entire face
10 of the resistor element 111, except on the first and second terminals 112 and 113, thereby completing the resistor in the nineteenth exemplary embodiment of the present invention.

15 The side face of the first and second terminals 112 and 113, after being connected to the resistor element 111, does not necessarily have a gap or space as shown in Fig. 27. For example, there may be no space, depending on the state of cold forging.

For adjusting the resistance of the resistor in the nineteenth exemplary embodiment of the present invention, a through groove may be created on the resistor element 111. Alternatively, a part of the surface and/or side of the resistor
20 element 111 may be cut by laser, punching, diamond wheel cutting, grinding, etching, and so on while measuring the resistance between predetermined points or calculating the required processing after measuring the resistance. The resistance may also be adjusted or corrected at the time of forming the resistor element 111.

5 If a material with a lower electrical conductivity than the resistor element 111 is used for the first and second terminals 112 and 113 in the resistor as manufactured above, dispersion in resistance due to variations in the measuring point increases, making it inappropriate for practical use. Accordingly, the first and second terminals 112 and 113 are made of a material having electrical conductivity greater than that of the resistor element 111.

Dispersion in resistance due to the position of the measuring point may also be reduced by making the thickness t of the first and second terminals 112 and 113 thicker than the thickness T of the resistor element 111.

10 Also, for suppressing temperature rise against heat generated by applying a current, the thickness t of the first and second terminals 112 and 113 is preferably made thicker than the thickness T of the resistor element 111.

15 The same effects are also achievable when the resistor in the nineteenth exemplary embodiment is manufactured with a process shown in Fig. 27 (c) implemented before the process shown in Fig. 27 (a), i.e., in the sequence of manufacture is shown as Fig. 27 (c), Fig. 27 (a), Fig. 27 (b), Fig. 27 (d), and Fig. 27 (e).

Twentieth exemplary embodiment

20 A resistor in a twentieth exemplary embodiment of the present invention is described below with reference to drawings.

Fig. 28 (a) is a sectional view, Fig. 28 (b) is a plan view, and Fig. 28 (c) is a sectional view taken along Line B-B in Fig. 28 (b) of the resistor in the twentieth exemplary embodiment of the present invention.

In Figs. 28 (a) to 28 (c), a resistor element 121 is typically made of a
 5 sheet of copper-nickel alloy, nickel-chromium alloy, copper-manganese-nickel alloy, or combination thereof. First and second concaved terminals 122 and 123 have a concave groove 124 of a width k equivalent to the thickness T of the resistor element 111. The entire surface of the first and second terminals 122 and 123 are coated with a low melting point metal 125 such as tin, tin lead alloy, tin
 10 silver alloy, tin antimony alloy, tin zinc alloy, tin bismuth alloy, silver zinc , alloy silver lead alloy, gold tin alloy, or zinc typically by plating. The first and second terminals 122 and 123 are electrically connected to both ends of the resistor element 111 in the groove 114 through the metal 125.

The thickness t of these first and second terminals 122 and 123 is
 15 thicker than the thickness T of the resistor element 121; their width m is equivalent to or wider than the width W of the resistor element 121; and their length w is shorter than the length L of the resistor element 121. The first and second terminals 122 and 123 are made of metals such as copper, silver, gold, or aluminum with the same or greater electrical conductivity than that of the resistor
 20 element 121. The metal 125 electrically connects the resistor element 121 and the first and second terminals 122 and 123. The metal 125 on the circumference of the first and second terminals 122 and 123 also acts as a connecting material when the resistor is mounted on a printed circuit board. Except for the first and second terminals 122 and 123, insulating protective film 126, typically made of epoxy
 25 resin, polyimide resin, or poly-carbodiimide resin, covers the entire face of the resistor element 121.

A manufacturing method of the resistor in the twentieth exemplary embodiment of the present invention as configured above, and is described next with reference to drawings.

5 The manufacturing method of the resistor in the twentieth exemplary embodiment is basically the same as that described for the resistor in the nineteenth exemplary embodiment using Fig. 27. More specifically, in a process shown in Fig. 27(e), the insulated protective film 126, is cut into a predetermined shape using processes such as cutting, punching, and pressing, and disposed on the top and bottom faces of the resistor element 121 (not illustrated). The insulated
10 protective film is thermal compression bonded to form the insulated protective film 126 on the entire face of the resistor element 121 except for the first and second terminals 122 and 123. A detail which differs in this process from the nineteenth exemplary embodiment process is the thickness of a film is increased for the purpose of leveling the insulated protective film 126 to the top and bottom face
15 level of the first and second terminals 122 and 123. Thus, pressing is required for adjusting the shape.

In the thermal compression bonding, the resistor element 121 may optionally be pressed for a period to bond the resistor element 121 to the insulated protective film 126, and then the insulated protective film 126 may be heated
20 without applying pressure to accelerate curing.

The manufacturing method of the resistor in the nineteenth exemplary embodiment of the present invention comprises a first process of forming a first and second metal terminals 112 and 113 into a concave shape, and then coating the metal terminals with a low melting point on their entire face of the terminals to
25 obtain the first and second terminals 112 and 113, a second process of creating the

metal sheet resistor element 111 whose shape is adjusted to obtain a predetermined resistance, and a third process of covering both ends of the resistor element 111 with the first and second terminals 112 and 113 by cold forging, and electrically connecting the resistor element 111 and the first and second terminals 112 and 113 by heating and cooling. The implementation of the third process enables reduction of contact resistance without deforming the bonded portion which may occur by welding. Thus the process improves electrical connectivity between the resistor element 111 and the first and second terminals 112 and 113, and eliminates the need for forming a bonding material for mounting the resistor onto a printed circuit board after initial coating, thereby improving the productivity.

Industrial applicability

As described above, the resistor of the present invention comprises a sheet metal resistor element and separate metal terminals electrically connected to both ends of the sheet resistor element. These terminals are made of metal having the same or greater electrical conductivity than that of the resistor element.

With the above configuration, resistance of the terminals can be made smaller than that of the resistor element because the terminals are made of a material having the same or greater electrical conductivity than that of the resistor element. This enables to reduce the proportion of resistance of the terminals in the entire resistor, allowing to ignore its effect on fluctuation of resistance due to deviation in measuring points of a resistance measuring terminal. The present invention can thus assure reproducibility of highly accurate measurement of resistance, providing the resistor which assures highly accurate measurement of resistance even if the measuring point is not precisely placed.

What is claimed is:

1. A resistor comprising:

a resistor element made of metal sheet; and

terminals made of different metal and electrically connected to both

5 ends of said metal sheet resistor element,

wherein said terminal is made of a material having electrical conductivity not less than that of said resistor element.

2. The resistor as defined in Claim 1, wherein said resistor element is

10 corrugated in a thickness direction of the metal sheet.

3. The resistor as defined in one of Claims 1 and 2, wherein said

terminal has a groove of a width equivalent to a thickness of said resistor element,

and said terminal has a width not less than a width of said resistor element, and a

15 length shorter than a length of said resistor element.

4. A resistor comprising:

a resistor element made of metal sheet;

an insulating sheet disposed at least on one of top face and bottom

20 faces of said resistor element; and

a terminal having a concave groove of a width equivalent to a sum of a thickness of said resistor element and a thickness of said insulating sheet, said terminal being electrically connected to said resistor element.

SubB17

000220" 0255050

5. The resistor as defined in Claim 4, wherein said terminal has a groove of a width equivalent to the sum of the thickness of said resistor element and the thickness of said insulating sheet, and said terminal has a thickness thicker than a sum of the thickness of said resistor element and the thickness of said insulating sheet, a width not less than a width of said resistor element, and a length shorter than a length of said resistor element.

6. A resistor comprising:
a resistor element made of metal wire; and
a metal terminal having a concave groove covering both ends of said resistor element; said terminal being electrically connected to said resistor element.

7. A resistor comprising:
a resistor element made of metal wire, said resistor element being bent into a cylindrical coil shape; and
a metal terminal having a concave groove covering both ends of said resistor element, said terminal being electrically connected to said resistor element.

8. A resistor comprising:
a resistor element made of metal wire, said resistor element being bent symmetrically to the left and right in one plane; and
a metal terminal having a concave groove covering both ends of said resistor element, said terminal being electrically connected to said resistor element.

9. A resistor comprising:

a plurality of resistor elements made of metal wire, said resistor elements being aligned not to electrically contact each other; and
a metal terminal having a concave groove covering both ends of said resistor elements, said terminal being electrically connected to said resistor elements.

5

10. The resistor as defined in one of Claims 6, 7, 8, and 9, wherein said terminal has a groove of a width equivalent to one of a thickness and diameter of said resistor element; said terminal has a thickness thicker than a total thickness of said resistor elements, a width not less than a width of said resistor element, and a length shorter than a length of said resistor element.

10

11. A resistor comprising:

a resistor element made of metal sheet; and

15 a metal terminal disposed at both ends of said resistor element, said terminal being electrically connected to said resistor element and having an L shape section face.

12. The resistor as defined in Claim 11, wherein a thickness of a portion of said terminal underneath said resistor element is thicker than that of a portion of said terminal contacting an end face of said resistor element.

20

13. A resistor comprising:

a resistor made of metal sheet;

25 an insulating sheet attached to at least one of top and bottom faces of said resistor element; and

5 14. A resistor comprising:

a metal terminal disposed at both ends of said resistor element, said terminal having a one-side-open section face with an inner space broader than its opening, and being electrically connected to said step of said resistor element at least at said inner space of the opening.

15 a resistor element made of metal sheet;
an insulating substrate; and

20 16. A resistor comprising:

a resistor element made of metal sheet;
an insulating substrate; and
four metal terminals formed in a way to electrically connect top and
bottom faces of said insulating substrate, said terminal on a top face of said insulating
substrate being electrically connected to said resistor element.

5

a metal resistor; and

10

15

20

a metal resistor element having a notch near both ends; and

25

wherein said resistor element and said terminal are electrically connected at least through said protrusion and said notch.

a metal resistor element having at least two through holes; and
a metal terminal having at least one protrusion with a same shape as

5 wherein at least one protrusion of said terminal is inserted to at least one through hole of said resistor element, and at least one face of said terminal is electrically connected to said resistor element.

24. The resistor as defined in one of Claims 1, 2, 4, 6, 7, 8, and 9,
15 wherein a thickness of said terminal is at least three times of that of said resistor
element.

25. The resistor as defined in one of Claims 1, 2, 4, 6, 7, 8, 9, 11, 13, 14, 18, 20, 21, and 22, wherein a second conductive metal is interposed between said resistor element and said terminal.

26. The resistor as defined in one of Claims 1, 2, 4, 6, 7, 8, 9, 14, 18, 20, and 22, wherein a protective film is formed on said resistor element.

7. The resis
and bottom

5

cturing
t ma
eterm
term
id te
nal

having a shape adjusted to obtain a predetermined resistance;

forming a block of metal terminal having a concave groove; and

electrically connecting said terminal and said resistor element by

10

method for manufacturing a resistor element made of metal having a predetermined resistance; said resistor element is mounted on a block of metal terminal having a predetermined resistance by connecting said terminal and the resistor element to both ends of said terminal to both ends of said terminal.

being adjusted to obtain a predetermined resistance;

machining said resistor element into a predetermined shape;

forming a block of metal terminal having a concave groove; and

electrically connecting said terminal and said resistor element by

fitting said concave groove of said terminal to both ends of said resistor element.

20

30. A method for manufacturing a resistor comprising:

forming a terminal made of a metal foil pattern with a predetermined shape, top and bottom faces of said terminal being electrically connected to a part of

dividing said insulating substrate into a predetermined shape;

1907 1908 1909 1910 1911 1912 1913 1914 1915 1916 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2

electrically connecting said resistor element to the metal foil pattern on the top face of said insulating substrate.

31. A method for manufacturing a resistor comprising:

10

creating at least two through holes at a predetermined position of said resistor element;

15

thickness direction; and

electrically connecting said resistor element and said terminal.

32. The method for manufacturing a resistor as defined in one of Claims 28, 29, and 31, wherein said terminal is electrically connected to both ends of said resistor element by one of pressing and caulking after fitting said concave groove to both ends of said resistor element.

25 33. The method for manufacturing a resistor as defined in one of Claims 28, 29, 30, and 31, wherein said step of electrically connecting said resistor element and said terminal comprises the steps of:

and

5

10

15

20

25

electrically connecting said resistor element and said terminal.

a resistor element made of metal sheet, said resistor element having a shape adjusted to obtain a predetermined resistance, and having one of at least two through holes, notches, grooves, and cavities;

10

a concave terminal whose entire face is coated with metal having a low melting point, said terminal being disposed at both ends of said resistor element through a groove of said terminal, and being electrically connected to said resistor element through said metal having a low melting point in said grove; and
an insulating film covering entire face of said resistor element excluding said terminal.

20 38. The resistor as defined in Claim 37, wherein said terminal has a thickness thicker than a thickness of said resistor element, a width not less than a width of said resistor element, and a length shorter than a length of said resistor element.

39. The resistor as defined in one of Claims 37 and 38, wherein electrical conductivity of said terminal is greater than electrical conductivity of said resistor element.

5 40. The resistor as defined in Claim 37, wherein a thickness of said insulating protective film is leveled with top and bottom faces of said terminal, and a width of said insulating protective film is within a width of said terminal.

10 41. A method for manufacturing a resistor comprising:
a first step of forming a terminal by processing a concave metal terminal and then coating entire face of said terminal with metal having a low melting point;
a second step of forming a resistor element made of metal sheet whose shape is adjusted to obtain a predetermined resistance;
15 a third step of electrically connecting said resistor element and said terminal by cold forging said terminal after covering both ends of said resistor element with said terminal, heating, and cooling;
a fourth step of forming an insulating protective film having a predetermined shape on entire face of said resistor element excluding said terminal.

20 42. The method for manufacturing a resistor as defined in Claim 41, wherein said first step of forming said terminal is implemented after said second step of forming said resistor element.

000229 03560550

Adc A4

ABSTRACT

The present invention relates to the resistors used for detecting current in a current-carrying circuit as a voltage, and aims to provides a resistor which assures highly accurate measurement of resistance even if the measuring point is not precisely placed. To obtain the above purpose, the resistor of the present invention comprises a sheet metal resistor element (11) and separate metal terminals (12),(13) electrically connected to both ends of the sheet resistor element(11). These terminals (12),(13) are made of metal having the same or greater electrical conductivity than that of the resistor element (11). With the above configuration, resistance of the terminals can be made smaller than that of the resistor element. This enables to reduce the proportion of resistance of the terminals in the entire resistor, allowing to ignore its effect on fluctuation of resistance due to deviation in measuring points of a resistance measuring terminal.